

MIXING PREAMPLIFIERS

iMIX 2 Multi-Zone Mixing Preamplifiers

Stereo two-zone mixing preamplifier.

iMIX 2

A stereo two-zone mixer preamplifier with digital source selector, volume, tone and balance controls. iMix 2 mixer preamplifier has all the main features necessary for audio installations: input gain control, phantom power on/off, input priority, tone, balance control and RS232 interface for remote control of main functions. With iMIX2 mixer preamplifier it is possible to create 2 stereo zone or 2 mono zone audio systems, with paging possibilities.



Technical Specifications	iMIX 2
Power supply	~ 230 V/ 50 Hz
AC power consumption	20 VA
Frequency response	10 Hz - 50 kHz
THD	< 0,01 %
Input impedance	RCA - 20 kΩ (unbalanced) Phoenix - 47 kΩ (balanced)
Input gain	Line -10 dB Mic -50 dB
Output	Zone - 1 maximum output level + 15dB, impedance - 10 kΩ Zone - 2 maximum output level + 15dB, impedance - 10 kΩ
Priority inputs	Input 4
Tone control	Bass ±12 dB, Treble ±12 dB
HUM & Noise	-87 dB
Crosstalk	- 50 dB @ 1 kHz
Dimensions	44 mm × 482 mm × 200 mm, 1U 19" Rack Mount
Weight	4 kg
Colour	Black (RAL 9017)